



## Higher Revenue

- Max. efficiency 99.6%, weighted efficiency 99.0%
- Allows more panels on each roof to achieve higher system yields

## Simple & Easy

- Supports installation in shade prone areas and in different directions
- Quick frame mount at warehouse, less rooftop installation time
- Supports remote module-level monitoring

## Safe & Reliable

- IP68, support outdoor application
- Communication through DC Power Line Communication
- Single module shutdown capability to secure people and assets safety

Technical Specification	SUN2000P-375W
	<b>Input</b>
Rated input power	375 W
Absolute maximum input voltage	80 V
MPPT operating voltage range	10-80 V
Max. input current	12 A
Max. efficiency	99.6 %
Weighted efficiency	99 %
Overvoltage category	II
	<b>Output</b>
Max. output voltage	80 V
Max. output current	15 A
Output bypass	Yes
	<b>Standard Compliance</b>
Safety	IEC62109-1 (class II safety)
RoHS	Yes
	<b>General Specification</b>
Maximum allowed system voltage	1000 V
Communication	PLC
Dimensions (W x L x H)	125*85*25.5 mm
Weight (including cables)	0.7 kg
Installation Part	PV module frame / Aluminum extrusion profile Optional
Input connector	MC4
Output connector	MC4
Output wire length	47 in / 1.2 m
Operating temperature/humidity range	-40 to 85 °C / 0-100 %
Protection rating	IP68
	<b>PV System Design Using A SUN2000L Inverter</b>
Minimum String Length	According to inverter design rules & PV module datasheet
Maximum String Length	
Maximum Power per String	